



# Super Bolt



The Super Bolt is a heavy duty case hardened bolt seal for applications requiring restricted access to the doors of trucks, containers, and railcars. Special/restricted removal tool is required for bolt removal. Recommended only for controlled movement applications.

## APPLICATIONS

- Rail Cars
- Containers
- Truck/Trailer Door

## FEATURES

- High strength, tamper-resistant steel bolt offers extreme durability in all conditions
- Bright zinc plating for corrosion resistance
- Metal locking end encased in a consecutively numbered and/or barcoded half shell and custom colored secondary half-shell
- Features a color coded ABS marking body and clear ABS protective marking cover
- Anti-spin locking joint option
- 'H' on half shell of housing that indicates 'High Security'

## MATERIAL

Body: Steel, zinc plated finish  
Bolt: Hardened steel  
Tensile strength: 6475 lb (28.8kN)

## DIMENSIONS

Length: 4" and 6" (102mm and 152mm)  
Bolt Diameter: 3/8" (9mm)

## STRENGTH CHARACTERISTICS

A-Head removal tool required for head removal of seal depicted.



Seals shown not actual size.

# Super Bolt



## MARKING/PRINTING

- Emboss/Stamp
- 6 Digits

## STANDARD COLORS

Bright Zinc Plating

## PACKAGING

100 seal per box

Box dimensions: 11" x 9" x 5" (279mm x 229mm x 127mm)

Carton Weight

4": 32 lbs. (14.5 kg) per box.

6": 37 lbs (16.8 kg) per box.

